



1-5/8" RADIAFLEX® RAY Cable, A-series

- RADIAFLEX® functions as a distributed antenna to provide communications in tunnels, mines and large building complexes and is the solution for any application in confined areas.
- Slots in the copper outer conductor allow a controlled portion of the internal RF energy to be radiated into the surrounding environment. Conversely, a signal transmitted near the cable will couple into the slots and be carried along the cable length.
- RADIAFLEX® is used for both one-way and two-way communication systems and because of its broadband capability, a single radiating cable can handle multiple communication systems simultaneously.
- This RADIAFLEX® radiating cable utilize a low-loss cellular polyethylene foam dielectric and a smooth copper outer conductor which offers a superior electrical performance together with good bending properties.



RAY cable, A-series

FEATURES / BENEFITS

- ➔ Superior electrical performance in 610 to 2700 MHz
- ➔ Optimized for 4G / 3G / 2G wireless services incl. LTE
- ➔ Optimized for mission critical (safety) wireless services (e.g. Tetra / GSM-Rail)
- ➔ Optimized for high frequencies and digital transmission
- ➔ Ultra wideband from 75 to 2700 MHz
- ➔ Low coupling loss variation
- ➔ Designed for a variety of in-tunnel applications

Technical Features

GENERAL SPECIFICATIONS

Size	1-5/8"
------	--------

ELECTRICAL SPECIFICATIONS

Max. Operating Frequency	MHz	2700
Cable Type		RAYS
Impedance	Ohm	50 +/- 2
Velocity	%	91
Capacitance	pF/m (pF/ft)	72 (21.9)
Inductance	μH/m (μH/ft)	0.18 (0.055)
DC-resistance inner conductor	Ω/km (Ω/1000ft)	1.62 (0.49)
DC-resistance outer conductor	Ω/km (Ω/1000ft)	1.47 (0.45)
Stop bands	MHz	540-610, 980-1705, 2200-2370

MECHANICAL SPECIFICATIONS

Jacket		JFN
Jacket Description		Halogen free, non corrosive, flame and fire retardant, low smoke, polyolefin
Slot Design		Groups of slope slots at short intervals
Inner Conductor Material		Corrugated Copper Tube
Outer Conductor Material		Overlapping Copper Foil
Diameter Inner Conductor	mm (in)	17.6 (0.69)
Diameter Outer Conductor	mm (in)	44.2 (1.74)
Diameter over Jacket	mm (in)	48 (1.89)
Minimum Bending Radius, Single Bend	mm (in)	700 (28)
Cable Weight	kg/m (lb/ft)	1.01 (0.68)
Tensile Force	N (lb)	1200 (270)
Indication of Slot Alignment		Guides opposite to slots
Recommended Clamp Spacing	m (ft)	1.5 (5)
Minimum Distance to Wall	mm (in)	80 (3.15)

TEMPERATURE SPECIFICATIONS

Storage Temperature	°C(°F)	-70 to 85 (-94 to 185)
Installation Temperature	°C(°F)	-25 to 60 (-13 to 140)
Operation Temperature	°C(°F)	-40 to 85 (-40 to 185)



1-5/8" RADIAFLEX® RAY Cable, A-series

ATTENUATION AND POWER RATING

Frequency MHz	Longitudinal loss dB/100m (dB/100ft)	Coupling Loss	
		50%, dB	95%, dB
75	0,54 (0,16)	69 (73)	78 (82)
150	0,77 (0,23)	78 (82)	90 (94)
610	1,65 (0,50)	72 (76)	75 (79)
700	1,80 (0,55)	66 (70)	70 (74)
800	2,03 (0,62)	63 (67)	67 (71)
900	2,48 (0,76)	59 (63)	60 (65)
960	3,03 (0,92)	57 (61)	58 (63)
1700	4,20 (1,28)	57 (61)	61 (65)
1800	4,15 (1,26)	58 (63)	62 (67)
1900	4,04 (1,23)	57 (61)	61 (66)
2000	4,15 (1,26)	58 (63)	62 (66)
2100	4,28 (1,31)	59 (63)	63 (67)
2200	4,72 (1,44)	60 (65)	64 (69)
2400	5,70 (1,74)	61 (65)	72 (75)
2500	4,20 (1,28)	65 (68)	76 (79)
2600	4,22 (1,29)	66 (70)	76 (80)
2700	4,30 (1,31)	67 (71)	75 (79)

TESTING AND ENVIRONMENTAL

Jacket Testing Methods	Test methods for fire behaviour of cable :
	IEC 60754-1/-2 smoke emission: halogen free, non corrosive IEC 61034 low smoke IEC 60332-1 flame retardant IEC 60332-3-24 fire retardant UL1666, ASTM E 662, NES711 and NES713

External Document Links

Notes

- ➔ Coupling loss as well as longitudinal attenuation of RADIAFLEX® cables are measured by the free space method according to IEC 61196-4.
- ➔ Coupling loss values are measured with a radial (below 450 MHz) or vertical (above 450 MHz) orientated dipole antenna.
- ➔ The coupling loss values given in brackets are average values of all three spatial orientations (radial, parallel and orthogonal) of dipole antenna.
- ➔ Coupling loss values are given with a tolerance of +5 dB and longitudinal loss values with a tolerance of +5%. Note: Measured values below nominal are better. They are not limited by any tolerance-range.
- ➔ In case of a conflict of operational and stop band, please contact RFS for further assistance.
- ➔ As with any radiating cable, the performance in building or tunnel environments may deviate from figures based on free space method.